

RECEIVED  
CENTRAL FAX CENTER

Appl. No. 10/530,096  
Amdt. Dated October 3, 2007  
Reply to Office Action of July 3, 2007

OCT 03 2007

**Amendments to the Claims**

This listing will replace all prior versions, and listings, of the claims in the application:

**Listing of Claims:**

**Claim 1 (Cancelled)**

**Claim 2 (Withdrawn):** A sealing material in combination with an automobile engine cam cover wherein the sealing material seals the automobile engine cam cover and comprises a cured product of a composition comprising (A) an acrylic polymer having at least one alkenyl group capable of undergoing hydrosilylation reaction, (B) a hydrosilyl group-containing compound and (C) a hydrosilylation catalyst as essential components.

**Claim 3 (Withdrawn):** A sealing material according to Claim 2, where a liquid acrylic polymer having a number average molecular weight  $M_n$  of 500 or more and a molecular weight distribution ( $M_w/M_n$ ) of 1.8 or less is used as component (A) of the composition.

**Claim 4 (Withdrawn):** A sealing material according to Claim 2, where the cured product of the composition has a Duro A hardness of 45 or less.

Appl. No. 10/530,096  
Amdt. Dated October 3, 2007  
Reply to Office Action of July 3, 2007

**Claim 5 (Withdrawn):** A sealing material according to Claim 2, in combination with a resin-made cam cover.

**Claim 6 (Withdrawn):** An automobile engine cam cover sealed by a sealing material for cam covers according to Claim 2.

**Claim 7 (Withdrawn):** A sealing material in combination with an automobile engine oil pan wherein the sealing material seals the automobile engine oil pan and comprises a cured product of a composition comprising (A) an acrylic polymer having at least one alkenyl group capable of undergoing hydrosilylation reaction, (B) a hydrosilyl group-containing compound and (C) a hydrosilylation catalyst as essential components.

**Claim 8 (Withdrawn):** A sealing material according to Claim 7, wherein a liquid acrylic polymer having a number average molecular weight  $M_n$  of 500 or more and a molecular weight distribution ( $M_w/M_n$ ) of 1.8 or less is used as component (A) of the composition.

**Claim 9 (Withdrawn):** A sealing material to Claim 7, wherein the cured product of the composition has a Duro A hardness of 45 or less (according to JIS K6253).

Appl. No. 10/530,096  
Amtd. Dated October 3, 2007  
Reply to Office Action of July 3, 2007

**Claim 10 (Withdrawn):** Automobile engine oil pan sealed by a sealing material for oil pans which comprises a cured product of a composition comprising (A) an acrylic polymer having at least one alkenyl group capable of undergoing hydrosilylation reaction, (B) a hydrosilyl group-containing compound and (C) a hydrosilylation catalyst as essential components.

**Claims 11-14 (Cancelled):**

**Claim 15 (Previously presented):** A sealing material in combination with an automobile wire harness wherein the sealing material seals the automobile wire harness and comprises a cured product of a composition comprising (A) an acrylic polymer having at least one alkenyl group capable of undergoing hydrosilylation reaction, (B) a hydrosilyl group-containing compound and (C) a hydrosilylation catalyst as essential components.

**Claim 16 (Currently amended):** A sealing material The combination according to Claim 15, wherein a liquid acrylic polymer having a number average molecular weight Mn of 500 or more and a molecular weight distribution (Mw/Mn) of 1.8 or less is used as component (A) of the composition.

**Claim 17 (Currently amended):** A sealing material The combination according to Claim 15, wherein the cured product of the composition has a Duro A hardness of 50 or less (according to JIS K6253).

Appl. No. 10/530,096  
Amdt. Dated October 3, 2007  
Reply to Office Action of July 3, 2007

Claim 18 (Currently amended): A sealing material The combination according to Claim 15, wherein not more than 100 parts by weight of a reinforcing agent or a filler is added to the composition on the basis of 100 parts by weight of sum total of components (A), (B) and (C).

Claim 19 (Cancelled)

Claims 20-31 (Cancelled)

Claim 32 (Currently amended): A sealing material The combination according to Claim 17, wherein not more than 100 parts by weight of a reinforcing agent or a filler is added to the composition on the basis of 100 parts by weight of sum total of components (A), (B) and (C).

Claim 33 (Cancelled)

Claim 34 (New): The combination according to Claim 15, wherein automobile wiring harness is combined with the cured product of the composition and the cured product of the composition has a tight adhesiveness to electrical wires, a low hardness, and a low insertion resistance to electrical wires.